



formula for calculating speed (spindle)

n		V _c	x	1000
"	_	D_c	x	π
14968 [rpm]	_	940 [m/min]	Χ	1000
14900 [lbiii]	=	20,0 [mm]	Х	3,14

validated cutting data for roughing

	randatoa outinig data ioi rouginiig									
Туре	D_c	Z _n	V_{c}	f _z	n	V_{f}	a_{e}	a_p	L ₁	L ₂
Type	[mm]	[number]	[m/min]	[mm]	[rpm]	[mm/min]	[mm]	[mm]	[mm]	[mm]
torus	20,0	2	435	1,500	6.927	20.780	10,00	20,00	86,0	20,0
torus	12,0	2	260	1,500	6.900	20.701	6,00	12,00	55,0	16,0
torus	6,0	2	130	1,500	6.900	20.701	3,00	6,00	23,0	8,0

formula for calculating axis feed rate

V_{f}	=	n	х	f _z	x	z _n
45000 [mm/min]	=	15000 [rpm]	Χ	1,500 [mm]	Х	2 [number]

validated cutting data for finishing

variation catting data to: miloting										
Type	D _c	Z _n	V _c	f _z	n	V_f	a _e	a_p	L ₁	L ₂
Туре	[mm]	[number]	[m/min]	[mm]	[rpm]	[mm/min]	[mm]	[mm]	[mm]	[mm]
ball	20,0	2	400	1,600	6.369	20.382	2,00	10,00	68,0	17,0
ball	12,0	2	240	1,600	6.369	20.382	1,20	6,00	52,0	10,5
ball	6,0	2	120	1,600	6.369	20.382	0,60	3,00	23,0	10,0

recommended cutting data for roughing

parameter	symbol	unit
radial infeed:	a_e	[mm]
axial infeed:	a_p	[mm]
number of teeth:	Z _n	[number]

roughing recommendation				
min.	ideal	max.		
- x D _c	0,50 x D _c	$0,80 \times D_{c}$		
0,10 x D _c	1,00 x D _c	$5,00 \times D_{c}$		
1	1	2		

parameter	symbol	unit
cutting speed:	V_c	[m/min]
feed/tooth:	f_z	[mm]
reca/tootin.	٠.۷	[]

user
specifications
selection in the diagram
selection in the diagram

calculation by user calculation by user

recommended	cutting	data	for	finishing

parameter	symbol	unit
radial infeed:	a_{e}	[mm]
axial infeed:	a_p	[mm]
number of teeth:	Z _n	[number]

finishing recommendation				
min.	ideal max.			
- x D _c	0,10 x D _c	0,80 x D _c		
- x D _c	0,50 x D _c	1,00 x D _c		
1	1	2		

speed (spindle):	n	[rpm]
axis feed rate:	V_{f}	[mm/min]

cutting diamet	ter: D _c	[mm]
tool total leng	ith: L ₀	[mm]
tool unclamping leng	jth: L ₁	[mm]
tool cutting leng	ıth: L ₂	[mm]

	processing specific
I	processing specific
ſ	processing specific
ľ	processing specific

RAMPF Advanced Polymers GmbH & Co. KG

Robert-Bosch-Str. 8 -10 l 72661 Grafenberg l Germany T +49.7123.9342-0 Our recommendations on the use of the material are based on many years of experience and current scientific and practical knowledge. They are, however, provided without any obligation on our part and do not relieve the buyer of the need for suitability tests. They do not constitute a legal relationship, nor are any protected third party rights what's ever affected thereby.



Cutting data diagram for milling RAKU[®] TOOL SB-0080





RAMPF Advanced Polymers GmbH & Co. KG

Robert-Bosch-Str. 8 -10 I 72661 Grafenberg I Germany T +49.7123.9342-0 E advanced.polymers@rampf-group.com Our recommendations on the use of the material are based on many years of experience and current scientific and practical knowledge. They are, however, provided without any obligation on our part and do not relieve the buyer of the need for suitability tests. They do not constitute a legal relationship, nor are any protected third party rights what's ever affected thereby.



Practical application of the cutting data RAKU[®] TOOL SB-0080



cutting data used on the demonstrator

sequence of processing	processing strategy	$a_{\rm e}$	a _p	offset	f _z	V _c
roughing torus D6	vol. roughing following contour	3,00	6,00	0,60	1,50	130
roughing torus D12	vol. roughing following contour	6,00	12,00	0,12	1,50	260
roughing torus D20	vol. roughing following contour	10,00	20,00	2,00	1,50	435
finishing ball D6	zigzag stroke milling	0,60	3,00	0,00	1,60	120
finishing ball D12	zigzag stroke milling	1,20	6,00	0,00	1,60	240
finishing ball D20	zigzag stroke milling	2,00	10,00	0,00	1,60	400

tools used on the demonstrator

tool manufacturer	tool type	D _c	L_0	L ₁	L_2	Z _n
hufschmied-tools.com/de/	PROTO-LINE / Torus	6,0	60,0	23,0	8,0	2
hufschmied-tools.com/de/	PROTO-LINE / Torus	12,0	100,0	55,0	16,0	2
hufschmied-tools.com/de/	PROTO-LINE / Torus	20,0	104,0	86,0	20,0	2
hufschmied-tools.com/de/	PROTO-LINE / Kugel	6,0	60,0	23,0	10,0	2
hufschmied-tools.com/de/	PROTO-LINE / Kugel	12,0	83,0	52,0	10,5	2
hufschmied-tools.com/de/	PROTO-LINE / Kugel	20,0	104,0	68,0	17,0	2





RAMPF Advanced Polymers GmbH & Co. KG

Robert-Bosch-Str. 8 -10 I 72661 Grafenberg I Germany T +49.7123.9342-0 Our recommendations on the use of the material are based on many years of experience and current scientific and practical knowledge. They are, however, provided without any obligation on our part and do not relieve the buyer of the need for suitability tests. They do not constitute a legal relationship, nor are any protected third party rights what's ever affected thereby.