

Feeds and Speeds for RAKU[®] TOOL MB-0600



formula for calculating speed (spindle)

$$n = \frac{V_c \times 12,0001}{D_c \times \pi}$$

$$15715 \text{ [rpm]} = \frac{3084 \text{ [ft/min]} \times 12,0001}{\frac{3}{4} \text{ [in]} \times 3,14}$$

formula for calculating axis feed rate

$$V_f = n \times f_z \times z_n$$

$$631 \text{ [in/min]} = 15715 \text{ [rpm]} \times 0,0201 \text{ [in]} \times 2 \text{ [number]}$$

validated cutting data for roughing

Type	D _c [in]	z _n [number]	V _c [ft/min]	f _z [in]	n [rpm]	V _f [in/min]	a _e [in]	a _p [in]	L ₁ [in]	L ₂ [in]
torus	¾	2	3084	0,0201	15.715	631	0,394	0,787	3,386	0,787
torus	½	2	1837	0,0179	14.043	503	0,236	0,472	2,165	0,630
torus	¼	2	919	0,0173	14.043	487	0,118	0,236	0,906	0,315

validated cutting data for finishing

Type	D _c [in]	z _n [number]	V _c [ft/min]	f _z [in]	n [rpm]	V _f [in/min]	a _e [in]	a _p [in]	L ₁ [in]	L ₂ [in]
ball	¾	2	3084	0,0256	15.715	804	0,008	0,079	2,638	0,669
ball	½	2	1837	0,0244	14.043	686	0,005	0,047	2,047	0,413
ball	¼	2	919	0,0240	14.043	675	0,002	0,024	0,906	0,394

recommended cutting data for roughing

parameter	symbol	unit
radial infeed:	a _e	[in]
axial infeed:	a _p	[in]
number of teeth:	Z _n	[number]

roughing recommendation		
min.	ideal	max.
- x D _c	0.50 x D_c	0.80 x D _c
0.10 x D _c	1.00 x D_c	2.00 x D _c
1	2	4

parameter	symbol	unit
cutting speed:	V _c	[ft/min]
feed/tooth:	f _z	[in]

user specifications
selection in the diagram
selection in the diagram

speed (spindle):	n	[rpm]
axis feed rate:	V _f	[in/min]

calculation by user
calculation by user

recommended cutting data for finishing

parameter	symbol	unit
radial infeed:	a _e	[in]
axial infeed:	a _p	[in]
number of teeth:	Z _n	[number]

finishing recommendation		
min.	ideal	max.
- x D _c	0.01 x D_c	0.10 x D _c
0,01 x D _c	0.10 x D_c	0.50 x D _c
1	2	4

cutting diameter:	D _c	[in]
tool total length:	L ₀	[in]
tool unclamping length:	L ₁	[in]
tool cutting length:	L ₂	[in]

processing specific
processing specific
processing specific
processing specific

RAMPF Group, Inc.


49037 Wixom Tech Drive | Wixom, MI 48393, USA
T +1.248.295.0223 | F +1.248.295.0224
E info.us@rampf-group.com

Our recommendations on the use of the material are based on many years of experience and current scientific and practical knowledge. They are, however, provided without any obligation on our part and do not relieve the buyer of the need for suitability tests. They do not constitute a legal relationship, nor are any protected third party rights what's ever affected thereby.

www.rampf-group.com



Feeds and Speeds for RAKU[®] TOOL MB-0600



RAMPF Group, Inc.

49037 Wixom Tech Drive | Wixom, MI 48393, USA
T +1.248.295.0223 | F +1.248.295.0224
E info.us@rampf-group.com

Our recommendations on the use of the material are based on many years of experience and current scientific and practical knowledge. They are, however, provided without any obligation on our part and do not relieve the buyer of the need for suitability tests. They do not constitute a legal relationship, nor are any protected third party rights what's ever affected thereby.

www.rampf-group.com



Feeds and Speeds for RAKU[®] TOOL MB-0600



cutting data used on the demonstrator

sequence of processing	processing strategy	a_e [in]	a_p [in]	offset [in]	f_z [in]	V_c [ft/min]
roughing torus D6	vol. roughing following contour	0,118	0,236	0,024	0,017	919
roughing torus D12	vol. roughing following contour	0,236	0,472	0,005	0,018	1837
roughing torus D20	vol. roughing following contour	0,394	0,787	0,079	0,020	3084
finishing ball D6	zigzag stroke milling	0,002	0,024	0,000	0,024	919
finishing ball D12	zigzag stroke milling	0,005	0,047	0,000	0,024	1837
finishing ball D20	zigzag stroke milling	0,008	0,079	0,000	0,026	3084

tools used on the demonstrator

tool manufacturer	tool type	D_c [in]	L_0 [in]	L_1 [in]	L_2 [in]	Z_n [number]
hufschmied-tools.com/de/	PROTO-LINE / torus	1/4	2,36	0,91	0,31	2
hufschmied-tools.com/de/	PROTO-LINE / torus	1/2	3,94	2,17	0,63	2
hufschmied-tools.com/de/	PROTO-LINE / torus	3/4	4,09	3,39	0,79	2
hufschmied-tools.com/de/	PROTO-LINE / ball	1/4	2,36	0,91	0,39	2
hufschmied-tools.com/de/	PROTO-LINE / ball	1/2	3,27	2,05	0,41	2
hufschmied-tools.com/de/	PROTO-LINE / ball	3/4	4,09	2,64	0,67	2



RAMPF Group, Inc.

49037 Wixom Tech Drive | Wixom, MI 48393, USA
T +1.248.295.0223 | F +1.248.295.0224
E info.us@rampf-group.com

Our recommendations on the use of the material are based on many years of experience and current scientific and practical knowledge. They are, however, provided without any obligation on our part and do not relieve the buyer of the need for suitability tests. They do not constitute a legal relationship, nor are any protected third party rights what's ever affected thereby.

www.rampf-group.com