

EP-2303, EP-2304 / EH-2936-2

Repair paste for boards

Fast cure at RT

Key Properties

- Sufficient pot life whilst fast curing
- Room temperature curing

Applications

- Repair of board materials

Processing Properties

		Unit	EP-2303	EP-2304	EH-2936-2
Color	visual		blue	green	white
Mix ratio	-	pbw	100	-	50
Mix ratio	-	pbw	-	100	50
Density	DIN 2811-1	g/cm ³	ca. 0.88	ca. 0.88	ca. 0.83

		Unit	EP-2303 / EH-2936-2	EP-2304 / EH-2936-2
Color		visual	blue	light green
Pot life at 25 °C	100 ml	min	15 - 20	15 - 20
Machinable		min	90 - 120	90 - 120

Processing

The processing temperature and material temperature should be between 20-25°C. Mix the two components thoroughly in the ratio indicated and apply by spatula.

Packaging

RAKU® TOOL EP-2303	5 kg
RAKU® TOOL EP-2304	5 kg
RAKU® TOOL EH-2936-2	0,50 kg

Storage

Original containers should be kept tightly sealed and stored at ambient temperatures (15°C to 30°C). If properly stored the products have the shelf-life indicated on the product label. Partly used containers should always be sealed appropriately and used up as soon as possible.